# **SPECIFICATION SHEET**

# LIPSTICK WM33I SERIES RANGE HOODS



When you see it you'll agree, there's no other name for it. LIPSTICK, the graceful cylinder, a splash of color, and a bold wedge that is so familiar yet completly uncommon.

### **FEATURES**

- Italian design
- Wall mount
- Finishes: 430 Stainless Steel, #4 Brushed, Red
- Width: 40 cm (15-3/4")
- Accommodates 8' to 9' ceilings (ducted and non-ducted components included)
- 6" round duct connector/backdraft damper
- 2-level halogen lighting (2 bulbs included. Type T3, G4 base, 12 volt, 20 watts max.)
- 4-speed joy-stick control with LED display
- Quiet, variable-speed centrifugal blower with high-efficiency motor produces 400 CFM of exhaust
- Perimeter aspiration provides smooth surface to ease cleaning
- Heat Sentry<sup>™</sup> automatically turns blower to high speed when excess cooking heat is detected
- Delay timer control automatically shuts off range hood after 10 minutes
- Filter clean reminder
- Dishwasher-safe filter features a quick-release latch
- For indoor use only

## **OPTIONS**

• Replacement charcoal filters available (Model AFCWM33)

### **SPECIFICATIONS**

VOLTS	HZ	AMPS	CFM		SONES		DUCT
			MAX.	NORM.	MAX.	NORM.	
120	60	3.12	400	200	7.0	3.0	6" Round





HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

BEST Hartford, Wisconsin www.BestRangeHoods.com 800-558-1711 BEST Drummondville, QC, Canada www.BestRangeHoods.com 866-737-7770

REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by Date	

