

LIEBHERR

Design Guide

Freestanding / Semi Built In Models 30", 36" and 60"

Liebherr's engineering excellence in Germany provides the largest selection of freezers, refrigerators and wine refrigerators worldwide.

Liebherr-appliances specializes in the manufacturing of high quality freezers and refrigerators. With more than 300 basic models, we have the widest selection in the world. Liebherr appliances feature premium quality, numerous innovative product ideas and advanced design. Liebherr freezers and refrigerators are manufactured at three modern production plants:

Liebherr Marica in Bulgaria, Liebherr-Hausgeräte Ochsenhausen GmbH in Germany and the Liebherr-Hausgeräte Lienz GmbH in Austria.

The appliances for the North American market are produced in Austria and in Germany.

Liebherr is committed to the protection of the environment and recognizes it as a critical priority. To guarantee an optimum and consistent implementation, all ecological aspects were observed and integrated into the quality control of Liebherr in compliance with DIN EN ISO 9001.

Liebherr's Commitment to the Environment

The components of Liebherr products can be recycled when the necessary resources are available. A concern for the environment and a desire to protect resources has led to increased levels of recycling year after year. When Liebherr manufactures products, it is essential that the recyclable recovery rate of the materials we use constantly increases.

Recycling is a common goal among all manufacturers, municipalities and recycling companies to protect our environment. Protecting the environment and producing products which have a low impact on the environment, is one of Liebherr's core values. When the time comes, please attempt to dispose of your old appliances in an environmentally safe and friendly manner.

Introduction

LIEBHERR WARRANTY PLAN

FULL TWO YEAR WARRANTY

For two years from the date of original purchase, your Liebherr warranty covers all parts and labor to repair or replace any part of the product which proves to be defective in materials or workmanship.

FULL FIVE YEAR WARRANTY

For five years from the date of original purchase, your Liebherr warranty covers all parts and labor to repair or replace any components that prove to be defective in materials or workmanship in the sealed system. The "Sealed System" means only the compressor, condenser, evaporator, drier and all connecting tubing.

LIMITED 6TH THROUGH 12TH YEAR WARRANTY

From the 6th through 12th year from the date of original purchase, your Liebherr warranty covers all parts that prove to be defective in materials or workmanship in the Sealed System (parts only).

For Service in the U.S.

Liebherr Service Center

Toll Free: **1-866-LIEBHER or 1-866-543-2437**

Email: Service-appliances.us@liebherr.com

PlusOne Solutions, Inc.

3501 Quadrangle Blvd, Suite 120
Orlando, FL 32817

For Service in Canada

Liebherr Service Center

Toll Free: **1-888-LIEBHER or 1-888-543-2437**

www.euro-parts.ca

EURO-PARTS CANADA

39822 Belgrave Road
Belgrave, Ontario, N0G 1E0
Phone: (519) 357-3320
Fax: (519) 357-1326

Contents

General Remarks

Safety Warnings	I
Electrical Requirements & Safety	II
IceMaker (if equipped)	III
Area Requirements	IV
Safety Regulations	V

Freestanding/Semi Built In Models

30" and 60" Models: CS 1400, CS 16..., SBS 32S1	1
36" Models: CS 2062, CBS 2062, CS 2060, CS 2061	3
Unit Dimensions	5
Cabinet Opening Dimensions 30" and 60" Models	7
Cabinet Opening Dimensions 36" Models	8
Ventilation Requirements 30" and 60" Models	9
Ventilation Requirements 36" Models	10
Front Clearance CS/CBS 2062	11
Front Clearance CS 2060, CS 2061	12
Door Swing Clearance CS/CBS 2062	13
Door Swing Clearance CS 2060, CS 2061	14
Accessories for Liebherr Freestanding - Semi Built In Appliances	15

General Remarks

I. Safety Warnings

PLEASE READ AND FOLLOW THESE INSTRUCTIONS

This design guide contains Warning and Caution statements. This information is important for planning a safe and efficient installation. Please refer to the Installation Manual specific to your model for complete installation instructions.

This design guide is intended for planning purposes and is not a replacement for your appliance's Use and Care Manual which contains important information on how to use Liebherr appliances.

Always read and follow all Warning and Caution statements!

WARNING!

**Warning indicates a potentially hazardous situation
which, if not avoided,
could result in death or serious injury.**

CAUTION!

**Caution indicates a potentially hazardous situation
which, if not avoided,
may result in minor or moderate injury.**

IMPORTANT

**This highlights information that is especially relevant
to a problem-free installation and operation.**

Make sure incoming voltage is the same as the unit rating.

To reduce the risk of fire, electric shock, or personal injury, the installation work and electrical wiring must be done by a qualified electrician in accordance with all applicable codes and standards, including fire rated construction.

To the Installer

It is very important that the guidelines and instructions are followed in this design guide to ensure proper installation and operation of the unit. The Installation Guidelines section contains important information for making sure the installation is correct. Read and understand all the information and installation guidelines in this manual before the unit is installed.

It is also very important to **know** the Safety Information.

General Remarks

II. Electrical Requirements & Safety

A 115 Volt, 60 Hz, 10 Amp (15 Amp for side-by-side installation) fused electrical supply is required. We recommend using a dedicated circuit for these appliances to prevent electrical overload. Comply with the National Electrical Code as well as local codes and ordinances when installing the receptacle.



WARNING!

Do not ground to a gas pipe. Check with a qualified electrician if you are not sure the appliance is properly grounded. Do not have a fuse in the neutral or grounding circuit.



WARNING!

ELECTROCUTION HAZARD

Electrical Grounding Required. This appliance is equipped with a three-prong(grounding) polarized plug for your protection against possible shock hazards.

- **Do not remove the round grounding prong from the plug.**
- **Do not use a two-prong grounding adapter.**
- **Do not use an extension cord to connect power to the unit.**
- **Do not use a power cord that is frayed or damaged.**

III. IceMaker (if equipped)

The icemaker is located in the freezer compartment. It must be connected to the water supply to function properly. The appliance must be level for the icemaker to function properly.

The water supply pressure requirements are different based on whether or not the supplied Liebherr water filter is installed. With the filter installed, the pressure must be in the range of 40-90 psi (2.8-6.2 bar). Without the filter installed the acceptable pressure range is 22-87 psi (1.5-6 bar).

Use a 1/4" OD copper line to connect the water supply to the solenoid valve. This is not supplied with the appliance. If you have hard water, we recommend you install a water softener. Also, a filter must be installed if the water contains solids such as sand. All equipment and devices used to supply the water to the appliance must comply with the current regulations for your geographical area.

Safety Instructions and Warnings

- Do not attach the water source while the appliance is connected to an electrical outlet.
- A shut-off valve, must be installed between the hose line and the main water supply so that the water supply can be stopped if necessary. Do not install the shut-off valve behind the refrigeration unit.
- The connection to the water supply may only be made by a trained and licensed plumber.
- The water quality must comply with the drinking water regulations for the geographical area where the appliance is located.
- The icemaker is designed exclusively to make ice cubes in quantities needed by a household and may only be operated with water appropriate for this purpose.
- All repairs and work on the icemaker may only be done by customer service personnel or other trained personnel.
- The manufacturer cannot accept liability for damage caused by equipment or water lines between the solenoid valve and the water supply.

General Remarks

IV. Area Requirements

Verify the following:

- Floors can support refrigerator's weight plus approximately 1200 pounds (544 kg) of food weight. Not all Liebherr products are designed for 1200 pounds (544 kg) of food. Some units are smaller and total weights may vary.
- Finished kitchen floor height is level. Refrigerator must be shimmed to the floor level, or levelled, to make sure, air vents are not obstructed.
- Remove anything attached to the rear or side walls that can obstruct refrigerator opening.
- Cutout dimensions are accurate.
- Electrical outlet is in correct location.

Do not install this unit next to any other refrigerator or freezer except another Liebherr model. Liebherr models are designed to allow side by side installation. They are equipped with a heating system to eliminate condensation when units are installed side by side. Installing this unit next to any other refrigerator or freezer can cause condensation or cause damage to the Liebherr unit.

IMPORTANT

To protect the refrigerator from possible damage, allow the appliance to stand 1 hour in place before turning the electricity on. This allows the refrigerant and system lubrication to reach equilibrium.



CAUTION!

The anti-tip bracket must be installed to prevent the unit from tipping after it is installed. Refer to chapter "Blocking For Safety" in the installation instructions.

V. Safety Regulations

The appliance complies with UL250 and CAN/CSA-C 22.2 No. 63 and is designed to cool, freeze, store food as well as make ice (if equipped). They are designed for household use.

These appliances are set to operate within specific ambient temperature limits according to their climate rating. These temperature limits should not be exceeded. The correct climate rating for your specific model is indicated on the model plate. (See Use & Care Manual.)

This is explained as follows:


Climate Rating	Set for Ambient Temperatures of
SN	50°F to 90°F (10°C to 32°C)
N	61°F to 90°F (16°C to 32°C)
ST	61°F to 100°F (16°C to 38°C)
T	61°F to 109°F (16°C to 43°C)
SN-ST	50°F to 100°F (10°C to 38°C)
SN-T	50°F to 109°F (10°C to 43°C)

- The refrigerant circuit has been tested for leaks.

Freestanding/Semi Built In Models

30" and 60" Models


The stainless steel doors on 30" and 60" appliances comes with a SmartSteel surface. SmartSteel significantly reduces the visibility of finger marks and thanks to the high-quality finish of the stainless steel, it is very easy to clean and far more scratch-resistant.



CS 1660

Energy Star:	qualified
Energy consumption p. a.:	431 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	15.5 cu ft (438 L)
Refrigerator:	11.3 cu ft (319 L)
Freezer:	4.2 cu ft (119 L)
Ice cube output:	2.2 lbs/24h
Ice cube stock:	3.3 lbs
Climate Rating:	SN-T
Door hinges:	right / reversible


- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- SmartSteel doors
- LED light column and LED freezer lighting



CS 1611

Energy Star:	qualified
Energy consumption p. a.:	431 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	15.5 cu ft (438 L)
Refrigerator:	11.3 cu ft (319 L)
Freezer:	4.2 cu ft (119 L)
Climate Rating:	SN-T
Door hinges:	left / reversible

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- SmartSteel doors
- LED light column and LED freezer lighting




CS 1640

Energy Star:	qualified
Energy consumption p. a.:	431 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	15.2 cu ft (431 L)
Refrigerator:	11 cu ft (312 L)
Freezer:	4.2 cu ft (119 L)
Ice cube output:	2.2 lbs/24h
Ice cube stock:	3.3 lbs
Climate Rating:	SN-T
Door hinges:	right / reversible

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- SmartSteel doors

Freestanding/Semi Built In Models


30" and 60" Models



CS 1400

Energy Star:	qualified
Energy consumption p. a.:	423 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	14 cu ft (396 L)
Refrigerator:	11 cu ft (312 L)
Freezer:	3 cu ft (84 L)
Climate Rating:	SN-T
Door hinges:	right / reversible

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- SmartSteel doors



SBS 32S1 (CS 1611 & CS 1660)


Energy Star:	qualified
Energy consumption p. a.:	862 kWh
Energy Supply:	115V / 60Hz / 5A
Total capacity:	30.9 cu ft (876 L)
Refrigerator:	22.5 cu ft (638 L)
Freezer:	8.4 cu ft (238 L)
Ice cube output:	2.2 lbs/24h
Ice cube stock:	3.3 lbs
Climate Rating:	SN-T

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- SmartSteel doors
- LED light column and LED freezer lighting

Freestanding/Semi Built In Models

36" Models


The 36" wide bottom mount refrigerator/freezers offer almost 20 cubic feet of capacity to meet all storage demands. Side swing doors or French doors for the refrigerator compartment and double freezer drawers on telescopic rails ensure convenient access as well as elegant esthetics. The French door series features also the model CBS 2062 with the patented BioFresh technology.



CS 2062

Energy Star:	qualified
Energy consumption p. a.:	452 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	19.5 cu ft (552 L)
Refrigerator:	13.5 cu ft (382 L)
Freezer:	6 cu ft (170 L)
Ice cube output:	3 lbs/24h
Ice cube stock:	6 lbs
Climate Rating:	SN-T

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- LED light column and LED freezer lighting




CBS 2062

Energy Star:	qualified
Energy consumption p. a.:	450 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	18.9 cu ft (535 L)
Refrigerator:	12.9 cu ft (365 L)
Freezer:	6 cu ft (170 L)
Ice cube output:	3 lbs/24h
Ice cube stock:	6 lbs
Climate Rating:	SN-T

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- LED light column and LED freezer lighting
- BioFresh drawers with adjustable humidity

Freestanding/Semi Built In Models


36" Models



CS 2060 (right hinged)

Energy Star:	qualified
Energy consumption p. a.:	452 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	19.5 cu ft (552 L)
Refrigerator:	13.5 cu ft (382 L)
Freezer:	6 cu ft (170 L)
Ice cube output:	3 lbs/24h
Ice cube stock:	6 lbs
Climate Rating:	SN-T

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- LED light column and LED freezer lighting




CS 2061 (left hinged)

Energy Star:	qualified
Energy consumption p. a.:	452 kWh
Energy Supply:	115V / 60Hz / 2.5A
Total capacity:	19.5 cu ft (552 L)
Refrigerator:	13.5 cu ft (382 L)
Freezer:	6 cu ft (170 L)
Ice cube output:	3 lbs/24h
Ice cube stock:	6 lbs
Climate Rating:	SN-T

- Automatic refrigerator defrosting
- Automatic freezer compartment defrosting
- Automatic IceMaker can be switched off
- LED light column and LED freezer lighting

Freestanding/Semi Built In Models

Unit Dimensions




Overall height can be increased on CS 14 and all CS 16 units by 5/8" (16 mm).

CS 1400

A = 73-1/4" (1860 mm)
B = 29-3/8" (747 mm)
C = 24-13/16" (630 mm)
D = 52-3/8" (1330 mm)
E = 31-1/8" (791 mm)


CS 1660, CS 1640

A = 79-1/2" (2020 mm)
B = 29-3/8" (747 mm)
C = 24-13/16" (630 mm)
D = 52-3/8" (1330 mm)
E = 31-1/8" (791 mm)



CS 1611

A = 79-1/2" (2020 mm)
B = 29-3/8" (747 mm)
C = 24-13/16" (630 mm)
D = 52-3/8" (1330 mm)
E = 31-1/8" (791 mm)




Overall height can be increased on SBS 32 units by 5/8" (16 mm).

SBS 32S1 (CS 1611 & CS 1660)

A = 79-1/2" (2020 mm)
B = 59-1/4" (1505 mm)
C = 24-13/16" (630 mm)
D = 52-3/8" (1330 mm)
E = 62-3/4" (1594 mm)

Freestanding/Semi Built In Models




Overall height can be increased on CS 20 units by 1-1/2" (40 mm).


Please allow for door swing clearance at locations next to a wall.

CS 2062, CBS 2062

- A = 3-9/16" (92 mm)
- B = 79-13/16" (2027 mm)
- C = 35-13/16" (910 mm)
- D = 24-1/4" (616 mm)
- E = 40-3/4" (1035 mm)
- F = 39-1/2" (1003 mm)




The maximum door opening angle is 145°.



CS 2060, CS 2061

- A = 3-9/16" (92 mm)
- B = 79-13/16" (2027 mm)
- C = 35-13/16" (910 mm)
- D = 24-1/4" (616 mm)
- E = 58-5/8" (1489 mm)
- F = 39-1/2" (1003 mm)




The maximum door opening angle is 145°.

Freestanding/Semi Built In Models

Cabinet Opening Dimensions - 30" and 60" Models

The appliance can be used freestanding or semi built-in.
If semi built-in, consider the cabinet opening dimensions.

The power cord comes out of the appliance top.
The location of the electrical outlet can be within
a radius of 90 inch from the appliance top center.



Freestanding/Semi Built In Models

Cabinet Opening Dimensions 36" Models

The appliance can be used freestanding or semi built-in.


If semi built-in, consider the cabinet opening dimensions specified below.

Minimum opening height for the **single** door 36" models (CS 2060 / CS 2061) is **80"**.

Minimum opening height for the **french** door 36" models (CS 2062 / CBS 2062) is **80-1/2"** to accommodate the top mounted hinges.

The requirements for water supply and electrical outlet are the same for both applications.

The position of the electrical outlet can be within the grey shaded areas or above the appliance.




IMPORTANT

With 24" depth cabinets, the water line opening must be in the location as shown as there will not be room to route a water line behind the appliance for risk of pinching.

Also, for this cabinet depth the electrical outlet cannot be behind the unit or the unit will not be able to be pushed all the way back into the opening.

With cabinets deeper than 24" there is room to fit the pipe behind the appliance and the wall so there are no requirements for the water line lead out position.



The cabinet opening height is 84" when using the decorative grille. The decorative grille is deliverable as accessory and is not required for proper operation of the appliance. All ventilation requirements are handled through the toe kick grille on the appliance and this decorative grille is intended to be used as a filler for pre-existing 84" openings.

See chapter **"Accessories for Liebherr Freestanding - Semi Built In Appliances"** page 15.

NOTE

The decorative upper grille attaches to the cabinets / gables on either side of it and not to the appliance itself nor any cabinet above.

Freestanding/Semi Built In Models

Ventilation Requirements 30" and 60" Models

Do not restrict the air flow. The opening can either be directly over the appliance ①, above the cabinet and below the ceiling ② or through a vent installed in a soffit ③.



The cabinet height as specified at **80"** (2032 mm) will create a **1-5/16"** (33 mm) gap above the appliance providing optimal air flow over the top of the appliance for its efficient operation.

To have the same air flow for CS 1400 appliances, the cabinet opening height must be **73-3/4"** minimum.

Be sure to consider the possibility of having to raise some of the leveling legs in order to level the appliance when installing. If you adjust the height of the appliance - it will effectively reduce air flow. Therefore leave yourself some room for adjustment.

IMPORTANT

The section between the freezer door and the floor must not be covered.





The refrigerator is designed to allow proper air flow when the appliance is installed up against the wall.

A minimum space of 1 1/2" is required behind the cabinet when venting above an upper cabinet which is installed flush to the top of the appliance.

Freestanding/Semi Built In Models

Ventilation Requirements 36" Models

CS/CBS 20 appliances dont need any ventilation openings in the cabinet. The required airflow is directed through the toe kick area.



It is important to use the provided cover grille for the ventilation opening. This opening must not be covered with a cabinet base.


Freestanding/Semi Built In Models

Front Clearance

Top Door Hinge Dimensions CS 2062, CBS 2062

When installing CS/CBS 20 units into a row of cabinets or wall units, use these dimensions to achieve a custom look with the cabinetry.


Consider the necessary clearance for the top door hinge with CS/CBS 2062 units.



Overall height can be increased by 1-1/2" (40 mm).

Freestanding/Semi Built In Models


Front Clearance CS 2060, CS 2061



Overall height can be increased by 1-1/2" (40 mm).


Freestanding/Semi Built In Models

Door Swing Clearance CS 2062, CBS 2062



Freestanding/Semi Built In Models




Door Swing Clearance CS 2060, CS 2061



Freestanding/Semi Built In Models

Accessories for Liebherr Freestanding - Semi Built In Appliances

Kits may be necessary to complete this unit's installation or to apply it in a different manner than its original intent. If a kit is necessary, contact your Liebherr retailer or distributor. All installation materials for accessories are included with the kits.

Image	Article number	Name of the item	For use with model
	9900 321-00	Decorative grille 84" recess height.	CS 2062 CBS 2062
	9900 277-00	Decorative grille 84" recess height.	CS 2060 CS 2061
	7440 002-00	Water filter	CS 2062 CBS 2062 CS 2060 CS 2061 CS 1660

Freestanding/Semi Built In Models

