



CDV-365

36" Drop In Cooktop

Professional chefs demand performance when they cook. Why shouldn't home chefs expect the same? The DCS Drop-In Cooktop features patented Dual Flow Burners™ that can deliver a fierce 17,500 BTU, yet also allow you to simmer for hours at just 140°.

Brushed Stainless Steel

A PEACE OF MIND SALE
24 Hours 7 Days a Week Customer Support
T 1.888.936.7872 W dcsappliances.com

Dimensions

Depth	21"
Height	^(A) 5 1/2"
Width	^(B) 36"

Specifications

Burner ratings

All burners can simmer as low as 140° F	•
Center burner	17500 Max. BTU/hr / 3000 Low. BTU/hr
Front and rear burners	11000 max/ 3000 min BTU/hr

Burners

Dual Flow Burners™	5
Sealed Dual Flow Burners™	•

Cleaning

Easy clean	•
------------	---

Gas Requirements

Minimum 5/8 inch diameter flex line	•
Pressure LPG	11" to 14" W.C.
Pressure Natural	6" to 9" W.C.

Performance

Designer fit	•
Ergonomic	•
Gas (All Models available in Natural or LP Gas)	•
Gas cooktop sealed cooking surface	•
Sealed	•

Power requirements

Circuit Supply Voltage	15 A
Supply Frequency	60 Hz
Supply Voltage	120 V
Wire	3

Recommended Accessories

CTGP - Drop-in Griddle Plate	•
------------------------------	---

Ventilation

	Minimum 600 CFM DD-36 -
Recommended	36" DownDraft ES36 - 36" E-Pro Vent Hood

SKU	71092
-----	-------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © 2016 DCS by Fisher & Paykel Appliances Limited

Other product downloads available at dcsappliances.com