

TANKLESS WATER HEATER

Natural Gas





Remote

SIGNATURE FEATURES



ENDLESS HOT WATEREndless Hot Water — Hot water when you need for as long as you need it.



ENERGY EFFICIENT

More energy efficient than standard gas tank water heaters.



COMPACT SPACE SAVINGS



PREMIUM STAINLESS STEEL

Durable premium stainless steel exterior.

EN19WI30LS

PRODUCT DIMENSIONS

 Height
 24-1/2"

 Width
 18-1/2"

 Depth
 9-1/2"

MORE EASY-TO-USE FEATURES

LIFETIME LIMITED WARRANTY

Lifetime Limited Warranty supported by a 1-year labor, 5-year parts and 12-year heat exchanger warranty to provide peace of mind

3+ BATHROOMS

Satisfy home hot water demand for 3 plus bathrooms with the powerful 199,900 BTUs.

LASTS UP TO 20 YEARS

Lasts up to 2 times longer than standard gas tank water heaters.

LED DIGITAL DISPLAY


Conveniently adjust temperature to your needs with the LED digital display.

Available in:





CONTROL PANEL FEATURES	
Hard-Wired Remote	Yes
Lockout	Yes
LED Digital Display	Yes
Flow Rate Display Mode	G / L
Temperature Display Mode	°F/°C
PERFORMANCE	
Energy Factor	0.92
BTU/H (Max.)	199,900
BTU/H (Min.)	16,000
Thermal Efficiency	95%
Maximum Flow Rate (GPM – Gallons Per Minute)	11.1
FEATURES	
Flow Meter Alarm	Yes
Freeze Prevention	Yes
Direct Electronic Ignition	Yes
Lightning Protection	Yes
Recirculation Compatible	Yes 100 105 110 115 120
Number of Temperature Settings with Remote (°F) (5° Increments)	100, 105, 110, 115, 120 125, 130, 135, 140
Power Cord Included	Yes
Warranty ¹	Yes
ADDITIONAL FEATURES	
NSF® Certified	Yes
ACCESSORIES	
Condensate Neutralizer Kit – PN# TWHNEUTRAL	Optional
Horizontal Concentric Vent Termination – PN# TWHHORCONC	Optional
Horizontal Installation Kit – PN# TWHHORKIT (Application Specific)	Required
Horizontal Vent Termination – PN# TWHHORHOOD (Horizontal Dual Penetration)	Optional
Quick Connect Cord – PN# TWHQCCORD (Multiple Units)	Optional
Vertical Installation Kit – PN# TWHVERTKIT (Application Specific)	Required
Vertical Vent Termination – PN# TWHVERTCAP (Vertical Dual Penetration)	Optional
SPECIFICATIONS	
Indoor Wall-Mounted	Yes
Condensing	Yes
Direct Vent (SV Convertible) Exhaust	Yes
Gas Connection Size	3/4" Threaded
Gas Inlet Location	Right Bottom
Water Connection Size	3/4" Threaded
Water Inlet/Outlet Location	Left Bottom
Water Supply Pressure Range	15 - 150 psi
Condensate Connection Size	1/2" Threaded
Condensate Drain Location	Left Bottom
Power Cord Location	Middle Bottom
Voltage Rating	120V, 60Hz
Intake/Exhaust Vent Diameter	3" or 4"
Primary Heat Exchanger	Copper Stainland Stanl
Secondary Heat Exchanger	Stainless Steel
Color –	S
Stainless Steel Shipping Weight (Approx.)	82 Lbs.
Snipping weight (Approx.) *Lifetime limited warranty supported by a 1-year labor, 5-year parts and 12-year.	



For complete Tankless Water Heater installation details, refer to Product Installation Guide on the web at electroluxappliances.com

Height	24-1/2"
Width	18-1/2"
Depth	9-1/2"

Performance Flow Chart

Temp Rise (F°)	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100
EN19WI30LS (GPM*)	11.1	10.6	9.3	8.4	7.4	6.8	6.2	5.8	5.3	5.0	4.6	4.4	4.1	3.9	3.7

*Gallons Per Minute

FOR WATER HEATING INQUIRIES, PLEASE CONTACT ELECTROLUX WATER HEATING AT 1-888-360-8557.



Electrolux Major Appliances, N.A.