

KMR 1136-3 G GD EDST/CLST RangeTop



- Professional design – 36 (914) in (mm) wide in stainless steel with Clean Touch Steel™ finishing
- Direct control – metal knobs with light ring
- Easy cleaning – ComfortClean dishwasher-safe grates
- Broad performance spectrum – burner w. up to 19,500 BTU (5.7 kW)
- Convenient and safe – automatic re-ignition for all burners

EAN: 4002516495437 / Material number: 11852460 / Old Material Number: 26113670USA

Heating type	
Fuel type	Gas
Construction type	
Rangetop	•
Design	
Casing	Stainless steel
Front panel	CleanSteel
Genuine metal knobs	•
Cast iron pot rest (matte black enameled)	•
Cooktop features	
ReStart	•
Ring features	
Number of gas burners	4
Number of griddle surfaces	1
1st cooking zone/cooking area	
Position	front left
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Max. rating in W	5700
Maximum power output in BTU/hr	19500
2nd cooking zone/cooking area	
Position	rear left
Type	High-speed burner
Minimum power output in BTU/hr	1200
Max. rating in W	2300
Maximum power output in BTU/hr	12500
3rd cooking zone/cooking area	
Position	Centered
Type	Griddle surface
Max. rating in W	5600
Maximum power output in BTU/hr	13000
4th cooking zone/cooking area	
Position	rear right
Type	High-speed burner
Minimum power output in BTU/hr	1700
Max. rating in W	2600
Maximum power output in BTU/hr	19500
5th cooking zone/cooking area	
Position	front right
Type	Ultra high-speed burner
Minimum power output in BTU/hr	1700
Maximum power output in BTU/hr	19500
Max. rating in W	5700
8th cooking zone/cooking area	
True Simmer function	•
Width of griddle surface in in.(mm)	10 1/4 (258)
Depth of griddle surface in in.(mm)	17 1/8 (434)
Control panel	
Operation via genuine metal knobs with backlit	•

KMR 1136-3 G GD EDST/CLST RangeTop



EAN: 4002516495437 / Material number: 11852460 / Old Material Number: 26113670USA

Cleaning convenience

Dishwasher-safe trivets

•

Single-piece cooktop surround

•

Technical data

Dimensions in mm (width)

36 (914)

Dimensions in mm (height)

7 5/8 (191)

Dimensions (depth) in in. (mm) with bullnose

27 1/4 (692)

Appliance depth in in. (depth) without bullnose

25 5/8 (650)

Total output in BTU/hr

84000

Weight in kg

152 (69)

Total rated load in kW

24.60

Voltage in V

120

Fuse rating in A

10


Number of phases

1

Power cord length in ft. (m)

3 (1.2)

KMR 1136-3 G GD EDST/CLST RangeTop



KMR1134, KMR 1135, KMR 1136 (Installation drawing)

1) Side view, 2) Front view, 3) Rear view, 4) Gas Connection, 5) Electrical connection