

PW302718

FEATURES

Heavy-duty stainless steel construction

Handfinished with hemmed edges and welded seams

Bright halogen lighting

Infinite speed blower control

Heat sentry for safety

Recessed controls for sleeker look

Blower required (internal, in-line or remote blowers available)

Heat lamps available for 27" deep models only – bulbs not included

Transition with backdraft minimizes backward flow of cold air

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

600 CFM In-Line Blower

38" high stainless steel backsplash with or without warming racks

6", 12", 18", 24" and 30" high stainless steel duct covers

Make-up air damper

Recirculating kit and filter for non-ducted applications (internal blower)

Accessories available through an authorized Sub-Zero dealer.
For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS


- 300 CFM Internal
- 450 CFM Internal
- 1100 CFM Inline
- 1200 CFM Remote
- 1500 CFM Remote
- 600 CFM Internal
- 900 CFM Internal
- 600 CFM Inline
- 600 CFM Remote
- 900 CFM Remote



PRODUCT SPECIFICATIONS

Model	PW302718
Dimensions	30"W x 18"H x 27"D
Weight	69 lb
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical or Horizontal
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



DIMENSIONS

