

PWC362418

FEATURES

- Heavy-duty stainless steel construction
- Handfinished with hemmed edges and welded seams
- Blower required (internal, in-line or remote blowers available)
- Recessed controls for sleeker look
- Infinite speed blower control
- Bright halogen lighting
- Heat sentry for safety
- Transition with backdraft minimizes backward flow of cold air
- Install with accessory duct cover for chimney-style hood
- Rigorously tested in our U.S. manufacturing facilities for decades of use
- Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

- 38" high stainless steel backsplash with or without warming racks
 - 6", 12", 18" and 24" high stainless steel duct covers
 - Make-up air damper
- Accessories available through an authorized Sub-Zero dealer.
For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS


- 300 CFM Internal
- 450 CFM Internal
- 900 CFM Internal
- 1100 CFM Inline
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote
- 600 CFM Internal



PRODUCT SPECIFICATIONS

Model	PWC362418
Dimensions	36"W x 18"H x 24"D
Weight	78 lb
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



DIMENSIONS

